


Aura Dunes Print RCT - Ceiling Tile

Acoustic Ceiling Tile (T frame compatible







Performance



Technical Information





Features

Absorption Range: 315 Hz to 4000 Hz Acoustic Class: A | (aw) = 0,9

Recycled PET absorption- Class 1 product according to the OEKO-TEX@ Standard 100.

This product is available in the following Fire Rate: FR | Fire Rated

PRODUCT COMPOSITION:

Aura Print Textures | Print Finishes (FR)

- Print Finishes

- Sound PET acoustic core - Euro Class B

* also available for imperial sized ceiling grids, upon request.

Metric Ceiling Grid | 600x1200mm

The PET core is a material made entirely from recycled PET plastic, that undergoes an environmentally-friendly transformation process into the non-woven acoustic core we use in this panel. To keep this process as efficient as possible, the thickness of the product may vary slightly (±3mm).

Dimensions:

FR - PP | 595x1190x20mm | 0.82 Kg



Aura Dunes Print RCT - Ceiling Tile

Acoustic Ceiling Tile (T frame compatible)

Aura Dunes Print is made entirely from recycled PET, a sustainable material with exceptional acoustic properties. This ceiling tile range offers a choice of high-resolution printed solid colours, patterns and textures that create stunning visuals effects – from abstract art to simulating real claddings and

These minimalistic lightweight panels drop easily on standard European ceiling grids, granting fast, effortless installation.

Product finishes

(FR - PP) PET Print Finishes



Aura Dunes Print



Purpose

- Improving speech intelligibility
- High frequency absorption

Recommended for

- Office
- Hospitality - Public Spaces
- Conference Room
- Auditorium